

# HA-RO complete (+EDI)

## Reverse-Osmosis-System

### Technical Information



- Ready-to-use DI- or pure water preparation system – Plug&Treat
- Fully equipped closet-system
- Compact, high-quality DI-water preparation as RO- or EDI-system
- Fully closed, noise-reduced closet-system
- Visualisation, operation and parameter setting of the whole system via central control cabinet with 10“ touch panel
- All necessary pre- and after-treatment-components integrated
- Connection to process control technique possible
- Electrical and operational upgrade to DI-water-supply of whole building
- Processing of measured data with SPS, regulation and processing devices for conductivity, temperature, pressure, UV-intensity and others not required
- All measuring sites calibrateable and adjustable
- All conductivity-gauges temperature-compensated
- Vertical, wear-free stainless steel-inline-high-pressure pump
- High-quality electrical and hydraulical components



# HA-RO complete (+EDI)

## Reverse-Osmosis-System



### Technical Data

Permeate Output:	80 - 500 l/h
Pure Water Quality:	5 - 15 $\mu\text{S}/\text{cm}^*$
Diluate Output (EDI):	60 - 440 l/h
Ultra-Pure Water Quality (EDI):	< 1 $\mu\text{S}/\text{cm}^*$
Double Softener:	2 x 60 $\text{m}^3/^\circ\text{dH}^{**}$
Brine Tank:	50 l
Tank Volume (internal):	80 l
RO-Fine Filter:	10" or 20"
Water Inlet:	DN 25
Water Outlet:	DN 25
Drain:	DN 50
Connection Voltage:	230 V/50 Hz
Raw Water Pressure:	3,0 - 6,0 bar
Raw Water Temperature:	5°C - 25°C
Ambient Temperature:	5°C - 30°C
Dimensions in mm (W x D x H):	1000 x 600 x 1900
Weight:	approx. 450 kg, depending on the version

\* depending on quality of untreated water

\*\*depending on the permeate and/or diluate performance